

# SMT-08

## Conformances

AWS A5.14/ ASME SFA5.14 ERNiMo-8  
 JIS Z3334 SNi1008 (NiMo19WCr)  
 KOGAS  
 ABS AWS A5.14 ERNiMo-8  
 DNV-GL VL1.5Ni up to VL9Ni  
 RS Manufacturer's Spec. (-196°C)

## Applications

- LNG storage tanks
- Oxygen, nitrogen and LNG carriers

## Features

- For the automatic welding processes for a LNG storage tank with a method of GTAW for vertical joints of side plates (ASTM A333, A334, A353, A553)
- Impact toughness at extra low temperature

## Typical Chemical Composition of the Wire (%)

C	Si	Mn	P	S	Cr	Ni	Mo	Fe	W
0.015	0.012	0.01	0.002	0.001	2.1	69.8	19.2	5.6	2.6

## Typical Mechanical Properties of All-Weld Metal

YS MPa(lbs/in <sup>2</sup> )	TS MPa(lbs/in <sup>2</sup> )	EL (%)	Temp °C(°F)	CVN-Impact Value J (ft-lbs)
-	725 (105,000)	38.0	-196 (-321)	150 (111)

## Typical Welding Parameters

Diameter, Polarity Shielding Gas	Amp. (A)	Volt. (V)
1.2mm (0.045 in) DC-(Auto-TIG)		
Ar	160	28
2.4mm (3/32 in) DC-		
Ar	110	12

## Welding Position

## Current

GTAW: DC-(Auto TIG)

## Shielding Gas

Ar

## Diameter / Packaging

Diameter	MIG	TIG
mm (in)	12.5kg (27.6lbs)	5kg (11lbs)
1.2 (0.045)	✓	
2.0 (5/64)		✓
2.4 (3/32)		✓
3.2 (1/8)		✓

SMW

SAW

GMW

GTW

FCW

Non-FERROUS

APPENDIX