



MIG-315

Heavy Duty Cycle 60% | Waveform Control | 4 rolls wire feeder | 50/60Hz | Generator Friendly

317.MIG-315

ARC STABILITY

Waveform control, for extra arc stability, even at low currents.

PROTECTION

Equipped with temperature, voltage and current sensors for high protection.



EFFICIENCY : $\geq 85\%$

FREQUENCY : 50/60Hz

INSULATION CLASS : H

PROTECTION CLASS : IP23

COOLING : AF

Power Supply Voltage (V)	3~380/400/440 $\pm 10\%$
Effective Current (A)	15
Rated Input Power (kW)	11
Rated Input Current (A)	24
Duty Cycle (40°C 10min)	40% @ 315A 60% @ 250 A 100% @ 200 A
Welding Current Range (A)	50~315
Welding Voltage Range (V)	13.5~30
No load Voltage (V)	20~40
Power Factor	0.7
Net Weight (kg)	25
Dimensions (mm)	618 x 240 x 445
Wire Diameter (mm)	Fe: 0.6/0.8/0.9/1.0/1.2 Ss: 0.8/0.9/1.0/1.2 Flux-Cored: 0.6/0.8/0.9/1.0/1.2



EXPERIENCE THE CONVENIENCE OF EVERYTHING UNDER ONE ROOF

At Lascentrum, you can find everything you need regarding products for welding and safety. Lascentrum has been established in 1988 and now imports a complete range of welding consumables, gouging electrodes, gas welding & cutting equipment, welding blankets, safety products and accessories.

CONTACT

Nieuwland Parc 1
2952 DA Alblasserdam,
The Netherlands

T:+31 (0)78 642 96 56
F:+31 (0)78 642 96 86

www.lascentrum.com
info@lascentrum.com

