

COMPACT 220 AC/DC



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

COMPACT 220 AC/DC

(1ph) · 230V ± 10% · 50/60 Hz	
TIG	MMA
3,7 KVA	7,5 KVA
70 V	70 V
5 ÷ 200 A	5 ÷ 200 A
200A @ 40% 160A @ 60% 125A @ 100%	200A @ 40% 160A @ 60% 125A @ 100%
H	
IP 22S	
255x530x400 mm	
25 / 23,6 Kg	

STANDARD CONFIGURATION

Part number	Description	
99805977K3A	COMPACT 220 AC/DC · Air	
99805978A	Power source	INCLUDED
23020157	TIG torch · ExperTig 26 · 4 mt · conn. 50 mm² · 3 Pin · Consumables KIT Ø 2,4 mm	
43205040	Welding cable with electrode holder MMA · 25 mm² 3 mt	
43210170	Ground cable · 25 mm² · 2 mt	
99805978K2A	COMPACT 220 AC/DC · H ₂ O	
99805978A	Power source	INCLUDED
99490021KA	Cooler unit SMART 230V 220AC/DC + tank CL 500 · 5 kg	
99900171A	Trolley · 2 wheels + shelves ECO	
23020161	TIG torch · ExperTig 18 R.A. · 4 mt · 50 mm² · 3 Pin · H ₂ O	
43205040	Welding cable with electrode holder MMA · 25 mm² 3 mt	
43210170	Ground cable · 25 mm² · 2 mt	