

COMPACT 220 AC/DC



FEATURES



TECHNICAL DATA

Input Voltage	
Power 60%	
U _o	
Amp. min-max	
Duty Cycle 40°C	
Insulation	
Protection degree	
Dimens. (LxWxH)	
Weight box/net	

COMPACT 220 AC/DC

(1ph) · 230V ± 10% · 50/60 Hz

	TIG	MMA
Power	3,7 KVA	7,5 KVA
U _o	70 V	70 V
Amp. min-max	5 ÷ 200 A	5 ÷ 200 A
Duty Cycle 40°C	200A @ 40% 160A @ 60% 125A @ 100%	200A @ 40% 160A @ 60% 125A @ 100%
Insulation	H	
Protection degree	IP 22S	
Dimens. (LxWxH)	255x530x400 mm	
Weight box/net	25 / 23,6 Kg	

STANDARD CONFIGURATION

Part number	Description	
99805977K3A	COMPACT 220 AC/DC · Air	
99805978A	Power source	INCLUDED
23020157	TIG torch · ExperTig 26 · 4 mt · conn. 50 mm ² · 3 Pin · Consumables KIT Ø 2,4 mm	
43205040	Welding cable with electrode holder MMA · 25 mm ² · 3 mt	
43210170	Ground cable · 25 mm ² · 2 mt	
22905114	Zero compensated flowmeter regulator · Argon	

Part number	Description	
99805978K2A	COMPACT 220 AC/DC · H₂O	
99805978A	Power source	INCLUDED
99490021KA	Cooler unit SMART 230V 220AC/DC + tank CL 500 · 5 kg	
99900171A	Trolley · 2 wheels + shelves ECO	
23020161	TIG torch · ExperTig 18 R.A. · 4 mt · 50 mm ² · 3 Pin · H ₂ O	
43205040	Welding cable with electrode holder MMA · 25 mm ² · 3 mt	
43210170	Ground cable · 25 mm ² · 2 mt	
22905114	Zero compensated flowmeter regulator · Argon	