

TP 220 XL



FEATURES



TECHNICAL DATA

Input Voltage

Power 60%

U_o

Amp. min-max

Duty Cycle 40°C

Insulation

Protection degree

Dimens. (LxWxH)

Weight box/net

TP 220 XL

(1ph) 230V ± 10% • 50/60Hz

MIG	MMA	TIG
7 KVA	7 KVA	7 KVA
35 V	65 V	65 V
20 ÷ 200A	5 ÷ 200 A	5 ÷ 200 A
200A @ 35% 140A @ 100%	200A @ 35% 120A @ 100%	200A @ 35% 120A @ 100%
H		
IP 22S		
255x600x460 mm		
29,6 / 25,4 Kg		

STANDARD CONFIGURATION

Part number	Description	
99820046KB	TP 220 XL PULSED	
99820046B	Power Source	INCLUDED
43210132	Ground cable · 25 mm ² · 3 mt	
43205098	Welding cable with electrode holder · 16 mm ² · 3 mt	
23000494	MIG torch · TRAFIMET ERGO PLUS 25 · 3 mt	
ALU KIT	· Contact tip · Ø 0,8 M8	
	· Contact tip · Ø 1,0 M8	
	· Swirl ring · M8	
	· Wire liner · Ø 1,0 - 1,2 mm · 3,5 mt	
	· Brass wire inlet tube · Ø 4,4 x 5 mm · L = 150 mm	
33805003	Drive roll · Ø 30 mm · 0,6 - 0,8 mm	
33805104	Drive roll for aluminium · Ø 30 mm · 0,8 - 1,0 mm	