

UNITECH PULSE 360



FEATURES



TECHNICAL DATA

Input Voltage	
Power 60%	
U _o	
Amp. min-max	
Duty Cycle 40°C	
Insulation	
Protection degree	
Dimens. (LxWxH)	
Weight box/net	

UNITECH PULSE 360

	(3ph) 400V ± 10% · 50/60Hz		
	MIG	MMA	TIG
	12,1 KVA*	10,3 KVA*	9,4 KVA*
	45 V*	60 V*	12 V*
	30 ÷ 350A*	20 ÷ 320 A*	5 ÷ 350 A*
	350A @ 45%* 300A @ 60%* 250A @ 100%*	320A @ 45%* 270A @ 60%* 240A @ 100%*	350A @ 45%* 300A @ 60%* 250A @ 100%*
	H		
	IP 23S		
		Power source 440x930x840 mm	
		Wire feeder 240x560x460 mm	
	-		

STANDARD CONFIGURATION

Part number	Description	
99855027K	UNITECH PULSE 360 + XP4 LCD · H₂O	
99850012	Power source NO LCD	INCLUDED
99420081	Wire feeder XP4 LCD · H ₂ O	
99900286	Wheels KIT X4 / H4 / XP4	
44890342	Interconnection cable · 70 mm ² · 5 mt · H ₂ O	
99490033K	Cooler unit UNITECH PULSE + tank CL 500 · 5 kg	
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	

*the data are preliminary and may change in the future