

SMT-7030

Conformances

AWS A5.7/ ASME SFA5.7 ERCuNi

JIS Z3341 YCuNi-3

ABS AWS A5.7 ERCuNi

Welding Position

Current

GMAW: DC+(Pulse)

GTAW: DC-

Shielding Gas

Ar, Ar + He

Diameter / Packaging

Diameter	MIG	TIG
mm (in)	12.5kg (27.6lbs)	5kg (11lbs)
1.0 (0.040)	✓	
1.2 (0.045)	✓	
1.4 (0.052)	✓	
1.6 (1/16)	✓	
2.0 (5/64)		✓
2.4 (3/32)		✓
3.2 (1/8)		✓

Features

- No preheat & PWHT required, maximum interpass temperature 150°C
- Contamination of the weld zone with foreign material, particularly any source of lead, tin or zinc must be scrupulously avoided to prevent weld metal cracking

Typical Chemical Composition of the Wire (%)

C	Si	Mn	P	S	Ni	Ti	Cu	Fe
0.02	0.10	0.8	0.001	0.001	31.0	0.4	67.0	0.6

Typical Mechanical Properties of All-Weld Metal

YS MPa(lbs/in ²)	TS MPa(lbs/in ²)	EL (%)	Temp °C(°F)	CVN-Impact Value J (ft-lbs)
-	500 (73,000)	30.0		

Typical Welding Parameters

Diameter, Polarity Shielding Gas	Amp. (A)	Volt. (V)
1.2mm (0.045 in) DC+		
Ar, Ar + He	160	28
2.4mm (3/32 in) DC-		
Ar	110	12