



MIG-350DP

Suitable for 5kg spool | MIG/MAG Double pulse | synergetic MIG/MAG | MMA | LIFT TIG

317.MIG-350DP

This portable industrial level double pulse machine is specially designed for narrow space and high working position. With his small size but powerful output capability, works at both 400V and 230V. When the input voltage is 400V, the output current can reach to 350A. The MIG- 350DP comes with various functions such as MIG/MAG double pulse, synergetic MIG/MAG, MMA and LIFT TIG and is suitable for 5 kg spool.

PROTECTION

Equipped with temperature, voltage and current sensors for high protection.

DIGITAL DISPLAY

Digital control of all the welding parameters.

ARC STABILITY

Waveform control,for added stability of the arc, even at low current.



FREQUENCY : 50/60Hz

INSULATION CLASS : H

PROTECTION CLASS : IP23

COOLING : AF

Power supply voltage (V)	230 V			400V		
Rated input power (KW)	MIG	MMA	TIG	MIG	MMA	TIG
Rated input current (A) max	6.9	7.6	4.8	6.2	6.2	4.2
Effective current (A)	29.8	33	21	24.8	32	20
Effective current (A)	14.9	16.5	10.5	13.5	17.5	10.9
Duty cycle (40°C 10 Min)	25%@300A	25%@300A	25%@300A	30%@350A	25%@350A	35%@350A
	60%@200A	60%@200A	60%@200A	60%@250A	60%@250A	60%@250A
	100%@150A	100%@150A	100%@150A	100%@ 190A	100%@190A	100%@190A
Welding Current Range (A)	40 ~ 350					
Welding Voltage Range (V)	10.4~ 34					
No load voltage (V)	89.4	67	14	71	84	14
Net Weight (kg)	20.4					
Dimensions (mm)	585 x 210 x 420					



EXPERIENCE THE CONVENIENCE OF EVERYTHING UNDER ONE ROOF

At Lascentrum, you can find everything you need regarding products for welding and safety. Lascentrum has been established in 1988 and now imports a complete range of welding consumables, gouging electrodes, gas welding & cutting equipment, welding blankets, safety products and accessories.

CONTACT

Nieuwland Parc 1
2952 DA Alblasserdam
The Netherlands

T: +31 (0)78 642 96 56
F: +31 (0)78 642 96 86

www.lascentrum.com
info@lascentrum.com

