

Nominal Diameter

7,4 = 43 mm²

Rectus Series

96

This coupling system has been developed specifically for the area of breathing protection. Coupling system with single-hand operation. High Flow valve for optimum flow and low pressure drop. Additional safety locking system. This safety lock prevents unintentional disconnection. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked. Tested according DIN EN 14593.

Series 96 with additional end connections available on request.

Dust Protections  (P. 250)
for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass nickel plated


Plug: Brass nickel plated or
Stainless Steel

Seals: NBR or FKM

Technical Description

Connecting Force 0 bar: 30 N




Connecting Force 6 bar: 105 N

Flow diagrams**Air**



Couplings – with valve




Series 96KS

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	19	65	12	23		96KSAK13BPN
	R 3/8	19	64	12	23		96KSAK17BPN
 <p>Female Thread</p>	G 1/4	19	60	10	23		96KSIW13BPN
	G 3/8	19	59	9	23		96KSIW17BPN
 <p>Hose Barb</p>	6 mm	19	78	25	23		96KSTF06BPN
	9 mm	19	78	25	23		96KSTF09BPN
	10 mm	19	78	25	23		96KSTF10BPN
	13 mm	19	78	25	23		96KSTF13BPN



Plugs – without valve

Series 96KS

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	14	42	12		Brass	96SSAK13MXN
	R 3/8	17	42	12		Brass	96SSAK17MXN
	G 3/8	19	38	9		Stainless Steel	96SSAW17RXX
 <p>Female Thread</p>	G 1/4	17	38	10		Brass	96SSIW13MXN
	G 3/8	19	38	10		Brass	96SSIW17MXN
 <p>Hose Barb</p>	6 mm		51	25	12	Brass	96SSTF06MXN
	9 mm		51	25	12	Brass	96SSTF09MXN
	13 mm		53	25	12	Brass	96SSTF13MXN

⚠ Please consider our security advices on the pages 12/13 ⚠