



TIG 200 AC/DC MV

Generator friendly | Wireless remote foot control | Up/down remote control torch

317.TIG-200AC/DC-MV

AC BALANCE CONTROL

AC balance control monitors the oxide and helps better cleaning during aluminum welding.

PROTECTIONS

Equipped with temperature, voltage and current sensors for high protection.

WAVEFORMS

Square wave, sine wave, triangular wave and trapezoidal wave are included.

SMART KNOB OPERATION

Easy and intuitive parameter selection with Smart Knob.



EFFICIENCY : $\geq 85\%$

FREQUENCY : 50/60 Hz

COOLING : AF

INSULATION CLASS : H

PROTECTION CLASS : IP23

Power supply voltage (V)	1x 90V ~ 275V			
	1 ~ 110		1 ~ 230	
	TIG	MMA	TIG	MMA
Rated input power (KW)	3.6	4.2	4.7	6.6
Rated input current (A) max	30	35	21	31
Effective current (A)	23	19	16	18
Duty cycle (40°C 10 Min)	60% 160A	30% 160A	60% 200A	35% 200A
		60% 110A		60% 140A
	100% 125A	100% 80A	100% 110A	100% 110A
Welding current range (A)	50 ~ 130	50 ~ 160	50 ~ 200	
Clearance effect (AC Tig)	15 ~ 50			
Net. weight (kg)	15			
Dimensions	492 x 189 x 350			
No load voltage	67			
Up/down slope	0 ~ 10			
Pre/post flow	0 ~ 2 / 0 ~ 10			
Pulse fre.	0.5 ~ 200			
Pulse with range	5 ~ 95			
AC Frequency (Hz)	50 ~ 250			



EXPERIENCE THE CONVENIENCE OF EVERYTHING UNDER ONE ROOF

At Lascentrum, you can find everything you need regarding products for welding and safety. Lascentrum has been established in 1988 and now imports a complete range of welding consumables, gouging electrodes, gas welding & cutting equipment, welding blankets, safety products and accessories.

CONTACT

Nieuwland Parc 1
2952 DA Alblasserdam,
The Netherlands

T:+31 (0)78 642 96 56
F:+31 (0)78 642 96 86

www.lascentrum.com
info@lascentrum.com

