



MIG-200DP-MV5

MIG, MMA, TIG(lift-arc) | MCU Control System | 90VAC ~ 275VAC | IP23 | Dual pulse

317.MIG-200DP-MV5

PFC TECHNOLOGY

Power factor more than 0.99 will save much energy.
Digital control of all the welding parameters.

PROTECTION

Equipped with temperature, voltage and current sensors for high protection.

DUAL PULSE

Allows to activate devoted pulse curves for aluminium, mild steel and CuSi3.



INSULATION CLASS	: H
PROTECTION CLASS	: IP23
POWER FACTOR	: 0.99
EFFICIENCY	: 80%
FREQUENCY	: 50/60Hz
COOLING	: AF

Power Supply Voltage (V)	90 VAC ~ 275 VAC					
	1-110V±10% 50/60 Hz			1-230V±10% 50/60 Hz		
	MIG	MMA	TIG	MIG	MMA	TIG
Effective Current (A)	4	3,5	4,3	6,2	6,2	4,2
Rated Input Power (kW)	33	28	31	27	30	20
Rated Input Current (A)	20	15	17	15	15	12
Duty Cycle (40°C 10min)	30%@140A	30%@110A	40%@150A	30%@200A	25% @200A	35%@200A
	60%@110A	60%@80A	60%@125A	60%@145A	60%@ 130A	60%@155A
	100%@85A	100%@65A	100%@95A	100%@110A	100%@100A	100%@120A
Welding Current Range (A)	40A ~ 140A	10A ~ 110A	10A ~ 150A	40A ~ 200A	10A ~ 200A	10A ~ 200A
Welding Voltage Range (V)	14 ~ 24					
No load Voltage (V)	70					
Net Weight (kg)	12					
Dimensions (mm)	510 x 215 x 400					
Wire Diameter (mm)	Fe: 0.8 / 1.0 / 1.2 Ss: 0.8 / 1.0 Flux-Cored: 1.0/1.2					



EXPERIENCE THE CONVENIENCE OF EVERYTHING UNDER ONE ROOF

At Lascentrum, you can find everything you need regarding products for welding and safety. Lascentrum has been established in 1988 and now imports a complete range of welding consumables, gouging electrodes, gas welding & cutting equipment, welding blankets, safety products and accessories.

CONTACT

Nieuwland Parc 1
2952 DA Alblasserdam,
The Netherlands

T: +31 (0)78 642 96 56
F: +31 (0)78 642 96 86

www.lascentrum.com
info@lascentrum.com

